

MAX K160S



Technical information:

Parameter	Unit	Value
Diameter	[mm]	160
Length	[mm]	2110
Weight	[kg]	203
Air consumption	[m ³ /min]	min 3,5
Working pressure	[bar]	7

Basic SET includes:

Mole diameter 160 mm (1), control power supply hose 20 m (2), oiler with control panel (3), hook tool (4), round tool (5), EkoMAX oil 5I (6)

Application:

Making holes diameter 160 mm. Inserting PE/PVC pipes directly behind the mole, diameter 110 mm - 125 mm, Ø140mm, Ø160mm. By using Calibrators is possible to make holes diameter 195mm, 219mm and inserting PE/PVC pipes diameter up to 200 mm. Installing steel pipes diameter up to Ø 406 mm.

Warranty:

24 months.

MAX K160S ACCESSORIES

Description	Illustration
Tool for inserting PE/PVC pipes Ø110-125, Ø140mm, Ø160mm with accessories	
Calibrators for making holes Ø195mm, Ø219mm and tools for inserting PE/PVC pipes diameter up to 200 mm	
Sets for installing steel pipes Ø133mm, Ø159mm, Ø219 mm, Ø273mm, Ø323mm, Ø406mm	
Soil Removal Tools Ø133mm, Ø159mm, Ø219mm, Ø273mm, Ø323mm, Ø406mm	
Optical set 2 m Optical set 3 m	
EkoMAX oil 5 liters EkoMAX oil 20 liters	
Compressor hose 10 rm Compressor hose 20 rm	

CONTACT:

tel.: +48 58 / 694 05 12
mobile: 607 451 268

fax: +48 58 / 694 05 96
mobile: 607 451 661

mail: kret@terma-max.com
mobile: 607 451 900